Version CD 2.27 Summary

Purpose of Release: This is a general release for the E1030, E1040 and E1035SF scanners.

Instructions for installing drivers using the ISO file (or for Silent Installation): For Windows 10 and 11, mount the ISO file as a drive. (Right click on the ISO file and select Mount) The ISO image is required for silent driver installation, execute the command *set_up.exe /s* from the root of the ISO via the command line in order perform a silent/unattended install.

Date: September 25, 2024

Versions:

CD Version:	2.27	
TWAIN:	24.13	
Driver:	15.32	
TWAINgui:	16.9	
HIPPO.dll:	52.7	
Device:	1.18	
DeviceManager:	13.53	
Firmware (scanLLD):	1.0.6.0_1.0.2.8	
ISIS driver:	1.0.12301.11002	
WIA:	15.22	
Scan Validation Tool:	24.2	
Passport and Integrated A4 Flatbed		
HIPPO.dll	52.9	
Device:	5.6	
DeviceManager:	13.35	
Firmware (scanLLD):	1.0.2.4_1.0.1.7	

Supported Operating Systems:

WINDOWS 10 (Versions: 22H2 & 21H1) WINDOWS 10 – x64 (Versions: 22H2, 21H2) WINDOWS 11 – x64 (Versions: 23H2 & 22H2) WINDOWS 2019 Server – 64 bit (Version: 1809) – Driver only – No Smart Touch WINDOWS 2022 Server – 64 bit – Driver only – No Smart Touch Ubuntu 64 Bit V20.04 & V22.04

Supported Models:

Kodak E1030, Kodak E1040, Kodak E1035SF(TWAIN Only)

New Features for CD 2.27:

1. Added self extracting EXE for silent installation

Known Issues:

None

Version CD 2.24.01 Summary

Purpose of Release: This is a general release for the E1030, E1040 and E1035SF scanners.

Instructions for installing drivers using the ISO file (or for Silent Installation): For Windows 10 and 11, mount the ISO file as a drive. (Right click on the ISO file and select Mount) The ISO image is required for silent driver installation, execute the command *set_up.exe /s* from the root of the ISO via the command line in order perform a silent/unattended install.

Date: June 10, 2024

Versions:

CD Version: 2.24.01	
TWAIN: 24.13	
Driver: 15.32	
TWAINgui: 16.9	
HIPPO.dll: 52.7	
Device: 1.18	
DeviceManager: 13.52	
Firmware (scanLLD): 1.0.6.0_1.0.2.8	
ISIS driver: 1.0.12301.1100	2
WIA: 15.22	
Scan Validation Tool: 24.2	
Passport and Integrated A4 Flatbed	
HIPPO.dll 52.9	
Device: 5.6	
DeviceManager: 13.35	
Firmware (scanLLD): 1.0.2.4_1.0.1.7	

Supported Operating Systems:

WINDOWS 10 (Versions: 22H2 & 21H1) WINDOWS 10 – x64 (Versions: 22H2, 21H2) WINDOWS 11 – x64 (Versions: 23H2 & 22H2) WINDOWS 2019 Server – 64 bit (Version: 1809) – Driver only – No Smart Touch WINDOWS 2022 Server – 64 bit – Driver only – No Smart Touch Ubuntu 64 Bit V18.04 and V20.04

Supported Models:

Kodak E1030, Kodak E1040, Kodak E1035SF(TWAIN Only)

New Features for CD 2.24:

2. none

Kodak alaris

Kodak E1030/40 Series Scanner Software Release Notes

Improvements for CD 2.24:

- 1. Future improvements to the auto-dark algorithm at start of each scan session for improved image quality.
- 2. Firmware changes so that if less than 9 button are configured in Smart Touch then only that number of buttons numbers are shown as options on the scanner OCP.
- 3. Corrected error where a scanner receives a U9 error at power boot

Known Issues:

- 1. ZIR-428: ISIS driver: the multifeed response PC sound can be intermittent based on what sound is selected to be played and the computer being used.
- 2. ZIR-348: Enabling BarCode reading when 50 DPI is selected results in an error and scanning will not occur
 - a. Solution: Use another imaging resolution.
- 3. ZIR-346: Setting Image Edge Fill (fill White or Black) to greater than 34 inches results in an error when scanning
 - a. Solution: set Image Edge Fill to less than or equal to 34 inches.

Version CD 2.23 Summary

Purpose of Release: This is a general release for the E1030, E1040 and E1035SF scanners.

Instructions for installing drivers using the ISO file (or for Silent Installation): For Windows 10 and 11, mount the ISO file as a drive. (Right click on the ISO file and select Mount) The ISO image is required for silent driver installation, execute the command *set_up.exe /s* from the root of the ISO via the command line in order perform a silent/unattended install.

Date: February 23, 2023

Versions:

CD Version:	2.23	
TWAIN:	24.13	
Driver:	15.32	
TWAINgui:	16.9	
HIPPO.dll:	52.7	
Device:	1.18	
DeviceManager:	13.52	
Firmware (scanLLD):	1.0.6.0_1.0.2.6	
ISIS driver:	1.0.12301.11002	
WIA:	15.22	
Scan Validation Tool:	24.2	
Passport and Integrated A4 Flatbed		
HIPPO.dll	52.9	
Device:	5.6	
DeviceManager:	13.35	
Firmware (scanLLD):	1.0.2.4_1.0.1.7	

Supported Operating Systems:

WINDOWS 10 (Versions: 22H2 & 21H1) WINDOWS 10 – x64 (Versions: 22H2, 21H2 & 21H1) WINDOWS 11 – x64 (Versions: 22H2 & 21H1) WINDOWS 2019 Server – 64 bit (Version: 1809) – Driver only – No Smart Touch WINDOWS 2022 Server – 64 bit – Driver only – No Smart Touch Ubuntu 64 Bit V18.04 and V20.04 Pardus 21.3 & 19.5 Mint 20.2

Supported Models:

Kodak E1030, Kodak E1040, Kodak E1035SF(TWAIN Only)

New Features for CD 2.23:

3. Added auto-dark algorithm at start of each scan session for improved image quality.

Improvements:

- 4. Fix U5 Errors with Plugging/Unplugging USB for ADF or Flatbed
- 5. Updated Japanese User Guide
- 6. Add Dutch language user guide to installer
- 7. ISIS: driver will now properly report a Cover Open message
- 8. The entire paper stack no longer must be removed from the input tray as part of multifeed recover process.

Known Issues:

- 4. ZIR-428: ISIS driver: the multifeed response PC sound can be intermittent based on what sound is selected to be played and the computer being used.
- 5. ZIR-348: Enabling BarCode reading when 50 DPI is selected results in an error and scanning will not occur
 - a. Solution: Use another imaging resolution.
- 6. ZIR-346: Setting Image Edge Fill (fill White or Black) to greater than 34 inches results in an error when scanning
 - a. Solution: set Image Edge Fill to less than or equal to 34 inches.

Version CD 2.3 Summary

Purpose of Release: This is a general release to add flatbed support and ISIS driver for the E1030, E1040 and E1035SF.

Instructions for installing drivers using the ISO file (or for Silent Installation): For Windows 10 and 11, mount the ISO file as a drive. (right click on the ISO file and select Mount) The ISO image is required for silent driver installation, execute the command *set_up.exe /s* from the root of the ISO via the command line in order perform a silent/unattended install.

Date: October 17, 2022

Versions:	

0115.		
CD Version:	2.3	
TWAIN:	24.13	
Driver:	1.14	
TWAINgui:	16.9	
HIPPO.dll:	52.7	
Device:	1.16	
DeviceManager:	13.47	
Firmware (scanLLD):	1.0.5.7	
ISIS driver:	1.0.12210.13001	
WIA:	15.22	
Scan Validation Tool:	24.2	
Passport and Integrated A4 Flatbed		
HIPPO.dll	52.9	
Device:	5.5	
DeviceManager:	13.33	
Firmware (scanLLD):	1.0.2.3	

Supported Operating Systems:

WINDOWS 10 (Versions: 21H2 & 21H1) WINDOWS 10 – x64 (Versions: 21H2 & 21H1) WINDOWS 11 – x64 (Versions: 21H2) WINDOWS 2019 Server – 64 bit (Version: 1809) – Driver only – No Smart Touch WINDOWS 2022 Server – 64 bit – Driver only – No Smart Touch Ubuntu 64 Bit V18.04 and V20.04

Supported Models:

Kodak E1030, Kodak E1040, Kodak E1035SF(TWAIN Only)

New Features for CD 2.3:

- 4. Add support for Integrated A4 and Passport Flatbeds
- 5. Add ISIS driver

Improvements:

9. ZIR-237: Setting maximum document length to 118 inches and scanning a 118 inch document results in a jam message, 117 inch document is the maximum document length in releases V1.0.

Known Issues:

- 7. ZIR-428: ISIS driver: the multifeed response PC sound can be intermittent based on what sound is selected to be played and the computer being used.
- 8. ZIR-348: Enabling BarCode reading when 50 DPI is selected results in an error and scanning will not occur
 - a. Solution: Use another imaging resolution.
- 9. ZIR-346: Setting Image Edge Fill (fill White or Black) to greater than 34 inches results in an error when scanning
 - a. Solution: set Image Edge Fill to less than or equal to 34 inches.

Version CD 1.0 Summary

Purpose of Release: This is the initial release of the TWAIN drivers for the E1030 and E1040.

Instructions for installing drivers using the ISO file (or for Silent Installation): For Windows 10 and 11, mount the ISO file as a drive. (right click on the ISO file and select Mount) The ISO image is required for silent driver installation, execute the command *set_up.exe /s* from the root of the ISO via the command line in order perform a silent/unattended install.

Date: September 30, 2022 **Versions:**

CD Version:	1.0
TWAIN:	24.13
Driver:	1.13
TWAINgui:	16.8
HIPPO.dll	52.6
Device:	1.14
DeviceManager:	13.42
Firmware:	1.0.5.7
ISIS driver:	N/A
WIA:	15.22
Scan Validation Tool:	24.1

Supported Operating Systems:

WINDOWS 10 (Versions: 21H2 & 21H1) WINDOWS 10 – x64 (Versions: 21H2 & 21H1) WINDOWS 11 – x64 (Versions: 21H2) WINDOWS 2019 Server – 64 bit (Version: 1809) – Driver only – No Smart Touch WINDOWS 2022 Server – 64 bit – Driver only – No Smart Touch Ubuntu 64 Bit V18.04 and V20.04

Supported Models:

Kodak E1030 and Kodak E1040

New Features for CD 1.0:

6. Initial release of the WIA and TWAIN drivers for ADF scanning

Improvements:

1. N/A

Known Issues:

10.ZIR-237: Setting maximum document length to 118 inches and scanning a 118 inch document results in a jam message, 117 inch document is the maximum document length in releases V1.0.